

Uniwell



LX-5600 series

The LX-5600's Exceptionally Bright and Wide Viewing Angle LCD screen with adjustable contrast levels is suitable for any operational environment.

Either regular or enlarged character size of a product description can be selected to display on the LCD screen, with a choice of Blue or White for the background color.

All items throughout the sales transaction can be viewed by scrolling function and any corrections can be swiftly made.

Information on LCD screen guides you through easy, accurate and complete product set-up of description, price, stock control, and other related information.

The LX-5600 offers advanced memory functions with a choice of Table Management or Clerk Interrupt system, under which multiple operators can work in turn with single key.

Memory Expansion enables ESF (Electronic Store & Forward) data to be stored for security control and sales analysis.

The standard interface allows communication with other LX terminals, kitchen/slip printers, and one of the peripherals such as PC, scanner or cashless payment system, etc. With an optional interface, other peripherals can be linked to create a desirable System Configuration.

The LX-5600 offers the ideal solution to numerous business sectors such as pub, bar, restaurant, cafe, and retail store with feature-rich firmware.

Table Management System: This system allows each separate transaction to be stored temporarily and picked up for additional orders. This is often used in restaurants for customers to add desserts, coffee and drinks to their original order without having to pay separately each time.

Clerk Interrupt System: Different operators can use LX-5600 for a sales transaction while other sales transactions are underway on the same ECR. Each operator's registrations are stored under that particular operator so when they log on again they are able to resume registrations.

Labor Management: Easily manage each clerk's time & attendance record. (Option)

ESF (Electronic Store & Forward): Transactions and operations made on the ECR are recorded in memory and printed out. (Option)

4 Arrangement Keys: Enable a user to perform a commonly used sequence of key presses by using just one key. One Arrangement key can provide up to 50 key steps.

PLU/Group sales per Clerk: Easy to find which clerk sold a pre-selected list of 20 products the most. With this feature, each clerk is motivated to sell more of those products.

Media & Preset tender: 25 media keys & 10 Preset tender keys such as \$10, \$20, \$50, \$100 available.



Hardware Specification

Printer	Type	Impact dot matrix without an auto cutter
	Speed	3 lines/sec
	Receipt/Journal Validation	24 columns/line 55 columns/line
	Paper roll	45 mm x φ 83 mm
	Keyboard	Stroke key Flat key
Display	Front (LCD)	Blue mode LCD with white LED back light Reversing display function 21 columns x 8 lines
	Rear (1-line)	12 digits numeric (standard)
Dimensions		405 (W) x 423 (D) x 285 (H) mm
Standard Interface	RS232C x 1	One of: PC communication, Scanner, Scale, Thermal slip printer, RAM data transfer, Journal data transfer, EFT terminal
	RS485 x 1	Inter Register Communication, Kitchen printer, Slip printer
Optional Interface	RS232C x 2	One of: PC communication, Scanner, Scale, Journal data transfer



Uniwell Corporation
 3-5-25, Tenma, Kita-ku, Osaka, Japan, 530-0043
 Tel: 81-6-6353-7021 & Fax: 81-6-6352-7104
 E-mail: uniwell@uniwell.com
 Web Site: http://www.uniwell.com